


1	2	3	4	5	6	7	8																																																																								
电气性能检测: 1.100%导通测试 2.高压测试:300V(AC),漏电流不大于2mA。 3.绝缘测试:300V(DC),芯线绝缘电阻不小于20MΩ	外观要求: 1.外观无变形 无缺胶 无缩水 线皮无破损。 2.五金头无刮花 无变形 插针无变形	技术要求: 1.使用的无铅环保焊锡丝。 2.线焊好后套上热缩管保护并吹塑	未注线长公差要求 单位 (mm)	版本	日期	变更说明																																																																									
			0-50 ± 5 500-2000 ± 30	V1.1	2026/1/7	线缆去除铝箔																																																																									
			50-200 ± 15 2000-5000 ± 50																																																																												
			200-500 ± 20 5000-10000 ± 100																																																																												
注: 批量作业前需由领班/技术员生产一条首件, 送品质 确认OK后, 方可开始裁线生产																																																																															
																																																																															
<p>焊线定义</p> <table border="1"> <thead> <tr> <th>P1</th><th>线材颜色</th><th>P2</th><th>定义</th></tr> </thead> <tbody> <tr><td>1</td><td>26awg灰</td><td>1</td><td>R-com</td></tr> <tr><td>2</td><td>26awg紫</td><td>2</td><td>R1+</td></tr> <tr><td>3</td><td>26awg白</td><td>3</td><td>R2+</td></tr> <tr><td>4</td><td>26awg棕</td><td>4</td><td>R3+</td></tr> <tr><td>5</td><td>26awg橙</td><td>5</td><td>OT3+</td></tr> <tr><td>6</td><td>26awg黄</td><td>6</td><td>OT2+</td></tr> <tr><td>7</td><td>26awg绿</td><td>7</td><td>OT1+</td></tr> <tr><td>8</td><td>26awg蓝</td><td>8</td><td>OT-com</td></tr> <tr><td>9</td><td>18awg红</td><td>9</td><td>48VDC+</td></tr> <tr><td>10</td><td>18awg黑</td><td>10</td><td>48VDC-</td></tr> <tr><td>外壳</td><td>屏蔽层</td><td>外壳</td><td></td></tr> </tbody> </table> <p>母针芯焊接端 焊接排序图</p>								P1	线材颜色	P2	定义	1	26awg灰	1	R-com	2	26awg紫	2	R1+	3	26awg白	3	R2+	4	26awg棕	4	R3+	5	26awg橙	5	OT3+	6	26awg黄	6	OT2+	7	26awg绿	7	OT1+	8	26awg蓝	8	OT-com	9	18awg红	9	48VDC+	10	18awg黑	10	48VDC-	外壳	屏蔽层	外壳																									
P1	线材颜色	P2	定义																																																																												
1	26awg灰	1	R-com																																																																												
2	26awg紫	2	R1+																																																																												
3	26awg白	3	R2+																																																																												
4	26awg棕	4	R3+																																																																												
5	26awg橙	5	OT3+																																																																												
6	26awg黄	6	OT2+																																																																												
7	26awg绿	7	OT1+																																																																												
8	26awg蓝	8	OT-com																																																																												
9	18awg红	9	48VDC+																																																																												
10	18awg黑	10	48VDC-																																																																												
外壳	屏蔽层	外壳																																																																													
<p>打包要求: 插头套气泡袋, 1PCS/袋, 包装袋规格26*20*12C</p>																																																																															
<p>BOM</p> <table border="1"> <tbody> <tr> <td>⑥</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr> <td>⑤</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr> <td>④</td><td>02.PHG.3B.010.CL82ZG</td><td>1</td><td>PCS</td><td></td><td></td><td></td><td></td><td></td></tr> <tr> <td>③</td><td>02.FUG.3B.010.CA92Z</td><td>1</td><td>PCS</td><td></td><td></td><td></td><td></td><td></td></tr> <tr> <td>②</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr> <td>①</td><td>18awg*2C+26awg*8C+屏蔽-灰白色 PVC-65A-OD:8.6</td><td>4.22</td><td>M</td><td>4220</td><td></td><td></td><td>mm</td><td></td></tr> <tr> <td>序号</td><td>物料规格/名称</td><td>数量</td><td>单位</td><td>裁线总长</td><td>前剥外皮</td><td>前剥芯线</td><td>后剥外皮</td><td>后剥芯线</td></tr> <tr> <td></td><td></td><td></td><td></td><td>序号</td><td></td><td></td><td></td><td>单位</td></tr> </tbody> </table>								⑥									⑤									④	02.PHG.3B.010.CL82ZG	1	PCS						③	02.FUG.3B.010.CA92Z	1	PCS						②									①	18awg*2C+26awg*8C+屏蔽-灰白色 PVC-65A-OD:8.6	4.22	M	4220			mm		序号	物料规格/名称	数量	单位	裁线总长	前剥外皮	前剥芯线	后剥外皮	后剥芯线					序号				单位
⑥																																																																															
⑤																																																																															
④	02.PHG.3B.010.CL82ZG	1	PCS																																																																												
③	02.FUG.3B.010.CA92Z	1	PCS																																																																												
②																																																																															
①	18awg*2C+26awg*8C+屏蔽-灰白色 PVC-65A-OD:8.6	4.22	M	4220			mm																																																																								
序号	物料规格/名称	数量	单位	裁线总长	前剥外皮	前剥芯线	后剥外皮	后剥芯线																																																																							
				序号				单位																																																																							
<p>图纸打印日期</p> <p>HVK 深圳市鸿万科电子有限公司</p> <table border="1"> <thead> <tr> <th>编号</th><th></th><th>名称</th><th></th></tr> </thead> <tbody> <tr> <td>制图</td><td></td><td>型号</td><td>3B.010插头线</td></tr> <tr> <td>审核</td><td></td><td>图号</td><td></td></tr> <tr> <td>版本</td><td>V1.1</td><td>日期</td><td></td></tr> </tbody> </table>								编号		名称		制图		型号	3B.010插头线	审核		图号		版本	V1.1	日期																																																									
编号		名称																																																																													
制图		型号	3B.010插头线																																																																												
审核		图号																																																																													
版本	V1.1	日期																																																																													
1	2	3	4	5	6	7	8																																																																								